

Your automatic baling solution

Specially designed to bale **bulky flexible packaging, paper trim, cardboard, printer's waste and many other fibrous products**. It is an ideal choice for warehouses, distribution centers, carton plants and document destruction facilities who have large-volume needs or want to save labor. The independent belting system ensures that each bale is tightly belted by steel wires automatically.



AUTO-TIE HORIZONTAL BALER BY STEEL WIRES

SERIES 1 // SHBA2-400. SHBA2-600. SHBA2-800. SHBA2-1000. SHBA2-1200

CUSTOMIZED // MADE-TO-ORDER MODELS ARE AVAILABLE

FEATURES

Steel Wire Belting

ensures that the bales are tightly belted

Automatic Compressing and Belting System

requires only one press on the start button

PLC Control System

simplifies the operation



Specifications

MODEL	SHBA2-400	SHBA2-600	SHBA2-800	SHBA2-1000	SHBA2-1200
Compressing force	40Tons	60Tons	80Tons	100Tons	120Tons
Feed opening size (L * H)	1200*720mm	1500*750mm	1800*800mm	2000*1000mm	2400*1100mm
Bale size (L is adjustable)	800*720*Lmm	850*750*Lmm	1100*800*Lmm	1100*1000*L mm	1100*1100*Lmm
Bale weight (approx.)	150-350kg	200-400kg	400-600kg	500-800kg	800-1200kg
Bale belting material	12# steel wire	12# steel wire	10# steel wire	10# steel wire	10# steel wire
Belting line	4lines	4lines	4lines	5lines	5lines
Voltage (customizable)	380V, 3 phase, 50Hz	380V, 3 phase, 50Hz	380V, 3 phase, 50Hz	380V, 3 phase, 50Hz	380V, 3 phase, 50Hz
Power	15kw	22kw	30kw	60kw	90kw
Machine weight (approx.)	7000kg	10000kg	15000kg	18000kg	21000kg
Overall dimension	4400*1870*1870mm	5200*2200*2100mm	6000*2480*2300mm	6600*2730*2300mm	7500*3050*2400mm

OPTIONAL EQUIPMENT

Conveyor	Used for conveying material into the machine
Cyclone feeding device	Used for sucking material of small pieces into the chamber of machine

* Unit bale weight depends on the material used and bale size you adjust