

# Your automatic baling solution

Specially designed to bale bulky flexible packaging, paper trims, cardboards, printer's waste and many other fibrous products. It is an ideal choice for warehouses, distribution centers, carton plants and document destruction facilities. Choose from our existing models or contact us for customized models today to meet your specific baling demands.

## AUTO-TIE HORIZONTAL BALER

**SERIES 1** // SHBA2-400. SHBA2-600. SHBA2-800. SHBA2-1000

**CUSTOMIZED** // MADE-TO-ORDER MODELS ARE AVAILABLE

### FEATURES

**Automatic Steel Wire Belting**  
produces tightly belted bales

**Automatic Compressing and Belting System**  
only need one push of the start button to complete the whole process

**PLC Control System**  
simplifies the operation and maximizes efficiency

**Automatic Material Conveying & Feeding System**  
is optional to maximize the throughput rate



### Specifications

	SHBA2-400	SHBA2-600	SHBA2-800	SHBA2-1000
Compressing force	40Tons	60Tons	80Tons	100Tons
Feed opening size (L * H)	1200*720mm	1500*1100mm	1600*1100mm	1600*1100mm
Bale size (L is adjustable)	L*720*800mm	L*1100*800mm	L*1100*800mm	L*1100*1100 mm
Bale weight (approx.)	200kg-400kgs	300-600kgs	400-700kgs	600-1000kgs
Bale belting material	12# steel wire	12# steel wire	10# steel wire	10# steel wire
Belting line	4lines	4lines	4lines	5lines
Voltage (customizable)	220-480V, 3phase, 50/60Hz	220-480V, 3phase, 50/60Hz	220-480V, 3phase, 50/60Hz	220-480V, 3phase, 50/60Hz
Power	15kw	22kw	37.5kw	45kw
Machine weight (approx.)	7000kgs	10000kgs	12000kgs	17000kgs
Overall dimension	5700*3100*2400mm	6500*3500*2500mm	8400*3900*4000mm	900*4000*4000mm

#### OPTIONAL EQUIPMENT

Conveyor	Used for conveying material into the machine
Cyclone feeding device	Used for sucking material of small pieces into the chamber of machine

\* Unit bale weight depends on the material used and bale size you adjust